




Features

- 15" All-in-One Panel PC POS terminal with bezel-free touch display
- Energy-efficient & Powerful Intel® 7th Gen. Core I processors
- Durable operation with fanless design
- Water & dust-proof front panel protection rated IP64
- USB ports on both sides of the screen for peripheral connections
- Easy access hard drive tray for installation
- Embedded 260 mm/sec high-speed thermal printer
- SII-RP-D10 and EPSON TM-m30 thermal printer compatible
- Optional VFD & 8", 9.7" customer display, 2D barcode scanner, MSR, iButton, WiFi

Specification



Model			PST750	
Display	LCD Display Size		15" eDP Panel	
	Max. Resolution		1024 X 768	
	Brightness /Support Color		350 cd/m ² , 16.7M colors	
Touch Panel	Type		5-wire analog Resistive or Projected Capacitive touch	
Processor	CPU/ Chipset		Intel® Celeron 3965U (Dual Core 2MB Cache, up to 2.20GHz) MOQ required	
			Intel® Core™ i3-7100U (Dual Core 3M Cache, up to 2.40 GHz)	
			Intel® Core™ i5-7200U (Dual Core 3M Cache, up to 3.10 GHz)	
			Intel® Core™ i7-7500U (Dual Core 4M Cache, up to 3.50 GHz)	
Memory			X 1 (DDR4-2133MHz SO-DIMM, up to 16GB)	
Storage			X 1 (2.5" SATAIII SSD)	
I/O Connectors	USB 2.0		x 2 (rear), x 2 (side)	
	USB 3.0		x 4 (rear)	
	Powered COM (RS232)		X 3 (DB9 Power COM RI/ 5V/ 12V selected by jumper)	
	Cash Drawer Port		x 1 (24V RJ11)	
	VGA		x 1 (DB15)	
	Audio	Internal Speaker	1 x 2W	
	LAN		x 1 (RJ45 10/100/1000 Base-T)	
	DC out		1 x 24V 4-pin connector for printer	
	DC in		Lockable 3-pin DC 19V	
Optional Peripherals			VFD / 8", 9.7" customer display / MSR / iButton / 2D barcode scanner / WiFi	
Power Supply			90W DC 19V 3-pin power adapter	
OS Support			Linux / Win 10 IoT Enterprise	
Environment	Temperature	Operation	32° to 95° F (0° to 35° C)	
		Storage	-4° to 140° F (-20° to 60° C)	
	Relative Humidity		20% to 80% non-condensing	
Dimension (W x H x D)			364 x 400 x 261	

Specifications subject to change without notice.



Aluminum housing with fanless design
IP64 compliant front panel



Small footprint for counter space saving



Easy access hard drive tray and with VESA mount support



Self-service terminal for information, self-ordering, digital reception, registration





USB ports on both sides of the screen for peripheral connections




Optional VFD & 8", 9.7" customer display

Mechanical Layout / Drawing

Unit: mm



I/O Interface



Power Switch DC 19V IN LAN USB 2.0 x 2 USB 3.0 x 4 RJ11 VGA COM1 COM2 COM3 24V Printer DC Out