

CHEETAH

RP-3468

RP-Series



Easy Maintenance



Space Saving



Splash-resistant on frontal



Drop-in paper loading

RP Series

Multi Function POS

The RP POS terminal saves your effort connecting the printer and keeps the counter clean and clear. with its quick-swap design, the printer module can be maintained in simple steps and is therefore the best solution for space-conscious environment.



MSR / SCR and i-Button optional



0°~90° Viewing angle

CHEETAH CONNECTION

136/90 M.5 Bangkrui-Jongthanom Rd., Mahasawad,
Bangkrui, Nonthaburi 11130 (Thailand)

www.cheetahpos.com

Specification

Model Name

RP-3468

CPU	Intel Celeron J4125 2.7Ghz
Memory	4GB DDR4 (Max 16GB)
Display	15" TFT-LCD with LED backlight (1024 x 768)
Touch Panel	Capacitive Touch panel
HDD	2.5" SATA HDD 320GB/120GB SSD
Expansion	2 x Mini PCI-E slot
OS Compatibility	Windows 10, Windows 11
External I/O Interface	
Serial Port	2 x External COM Ports
VGA Port	1 x VGA (DB15)
Audio Port	1 x Line in, 1 x Line out
Ethernet Port	1 x RJ45 10M/100 M/1G Base-T
USB Port	4 x USB 2.0 Type A, 2 x USB 3.0 Type A
DC output Jack	1 x 12V/2.5A DC Jack
Optional Peripheral	
Magnetic Card Reader	ISO 7811 option 1/2/3 track
Wireless LAN	802.11 b/g
Customer Display	VFD / LCD Customer Display
Second Display	8 inch / 10 inch / 12 inch / 15 inch TFT-LCD display/non-touch
Control / Indicator	
Power Button	1
Powering	
Power support	AC 100V~240V / 60W power adapter (Optional 90W Adapter)
Environment	
EMC & Safety	CE/FCC Class A
Operating Temperature	5°C ~ 40°C
Storage Temperature	-20°C ~ 60°C
Operating Humidity	15%~80% RH
Storage Humidity	20% ~90% RH
Mechanical	
Housing Color	Black
Construction	ABS + SECC
Dimension(WxDxH)	400 x 225 x 320 mm
Weight	N.W. 8.5 kg
Printer	
Printing	Direct Thermal Printing
Total dots per line	576 dots
Dot density	8 dot/mm
Paper width	80 mm
Printing width	72 mm
Printing speed	180 mm/s
Paper loading type	Drop-in easy loading
Paper feeding pitch	0.0625 mm